



Nutech Paint

For a perfect finish!

EPiC
Aqua Epoxy
product guide



Australian
Owned & Made

Nutech

nutechpaints.com.au




EPiC Aqua Epoxy - 2 Pack System


Nutech Aqua Epoxy is a high strength two-pack coating which provides excellent protection for concrete, masonry, timber and primed metal surfaces. The coating provides hardness and scuff resistance, designed for a wide range of applications including warehouses, showrooms, hospitals, schools and prisons. EPiC Aqua Epoxy is only suitable for indoor use.

Key Features

- Low odour, low VOC and Greenstar compliant
- Hard wearing
- Excellent adhesion and chemical resistance
- High abrasion and impact resistance
- Resistant to vehicle traffic and hot tyre pickup
- Self sealing



Neutral Grey N23




Light Grey N35



Dark Grey N64



Birch Grey N25




Sand Y44




Terracotta



Slate G64



White



Black

Application Guide

Preparation

All surfaces must be free from rust, oil, grease and any other contamination. New concrete must have had 28 days to cure. All concrete should be etched using Nu-EcoSafe Etch (dilution 10:1 for smooth concrete and 15:1 for rough as on label). High pressure wash the surface and allow to dry completely. Painted concrete in poor condition should be stripped using the Nu-EcoSafe range of strippers.

Mixing

Mix 3:1. Pour part B into part A and stir thoroughly using a drill mixer. Do not hand mix.

Pot Life

Mixed EPiC Aqua Epoxy has a pot life of 2 hours. Do not use after the pot has expired. The application rate is 8-10m²/litre. For best results use two coats.

Application

Apply with a brush, roller or spray system. When coating bare masonry or concrete thin the first coat by 20%. Do not thin additional coats. Dilute and clean up with water.

Distributors:



Manufacturing & Sales
NUTECH PAINT PTY LTD
4 Keppler Cct, Seaford, VIC
Australia 3198
☎ 03 9770 3000
📞 03 9775 1680



sales@nutech.com.au

www.nutechpaints.com.au