

Quick Reference Roof Coating Guide

Product	Thinning	Compatible with	Recoat @ 20°C	Internal	External	Uses	Additional	Application Rate per coat	Tip Size
Primers & Sealers									
NuPrime	No Dilution	All roof top coats	1 hour	Yes	Yes	Powdery oxidised roof tiles and paint	Saturation coating milky dries clear	1 coat @4sq.m/litre	517-521
SupaPrime	No Dilution	All roof top coats	1-2 hours	Yes	Yes	Powdery oxidised roof tiles and paint	Saturation coating milky dries clear	1 coat @4sq.m/litre	519-521
Master Sealer	No Dilution	All roof top coats	1-2 hours	Yes	Yes	Stable cement roof tiles and paint	Saturation coating milky dries clear	1 coat @4sq.m/litre	519-521
Nubond	No Dilution	All roof top coats	2-4 hours	Yes	Yes	Rough, porous roof tiles and gloss enamel	Milky dries clear	1 coat @4sq.m/litre	519-521
Flexible Membrane (Elastomeric Barrier Coat)	No Dilution	All roof top coats	2-4 hours Not same day in cool/wet conditions	Yes	Yes	Unstable previously painted surfaces	Can be tinted to most colours	1 coat @4sq.m/litre	523-525
GP Primer	No Dilution	All roof top coats	2-4 hours Not same day in cool/wet conditions	Yes	Yes	Very rough cement roof tiles	Light Grey colour	1 coat @4sq.m/litre	523-525
Metal Primer	No Dilution	All roof top coats	2-4 hours Not same day in cool/wet conditions	Yes	Yes	Metal sheet roofing	Light Grey colour	1 coat @ 5-6sq.m/litre	523-525
Elite Terracotta Primer	No Dilution	All roof top coats	1-2 hours	Yes	Yes	Raw uncoated, Glazed & Vitrified Terracotta Tiles	Milky White	1 coat @5-12sq.m/litre Substrate dependent	519-521
Asbestos Sealer	No Dilution	All roof top coats	1-2 hours	Yes	Yes	Asbestos sheeting	Opaque White	1 coat @4sq.m/litre	519-521
Top Coats									
NuFlex	No Dilution	All roof Primers & Sealers	1-2 hours	Yes	Yes	Trade Quality	10 year warranty	2 coats @4sq.m/litre	519-521
TileFlex	No Dilution		1-2 hours	Yes	Yes	Premium Quality	12 year warranty	2 coats @4sq.m/litre	519-523
NXT Cool Zone (Gloss & Low Sheen)	No Dilution		1-2 hours	Yes	Yes	Ultra Premium Heat Reflective	15 year warranty	2 coats @4sq.m/litre	519-523
FlexiShield (Low Sheen & Matt)	No Dilution		1-2 hours	Yes	Yes	Mainly for Metal Surfaces	10 year warranty	2 coats @5sq.m/litre	519-521
Waterproofing									
Aqua Stop Silicon Sealer	No Dilution	Silicon in water	1 hour	Yes	Yes	Most porous surfaces	Do Not allow to pool on surface	2 coats @1-3sq.m/litre depending on substrate	515-519

* This is a quick reference guide only

** Primers and Sealers must be top coated

*** For complete information on all products refer to Nutech Product Data Sheets, Application Guidelines and Material Safety Data Sheets